

View Online at <https://aerobasegroup.com/nsn/5905-00-061-8162>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.938 inches

**Shaft Diameter:**

0.266 inches

**Shaft Length:**

1.188 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.875 inches

**Undercut Diameter:**

0.188 inches

**Shaft Style:**

Round, stepped

**Actuator Type:**

Dual concentric

**Undercut Length:**

0.875 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

500.0 kilohms 1st section

**Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

0.5 free air 1st section

**Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 all sections

**Standard Taper Curve Per Section:**

F 2nd section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0