Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-063-8300

# Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.625 inches

#### **Body Diameter:**

0.250 inches

**Body Length:** 

0.250 inches

#### Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

215.0

## Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Left adjacent side two rows

#### **Mounting Method:**

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

20.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

270.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

## Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0