NSN 5905-00-063-9004

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-063-9004

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0 Electrical Resistance: 0.500 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Electrical Resistance: 0.500 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
0.500 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 165.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Between 1.875 inches and 2.125 inches Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Body Diameter: 0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
0.281 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
0.688 inches Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
2.000 free air Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
Cubic Measure (non-core): 0.043 cubic inches Style Designator: Axial terminal each end
0.043 cubic inches Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Obalf Life.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Film
Fiig:
A001a0