

View Online at <https://aerobasegroup.com/nsn/5905-00-064-0761>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.655 inches

First Flat Length:

0.625 inches

Flat Height:

0.216 inches

Body Diameter:

3.190 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.780 inches

Overall Diameter:

3.785 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Maximum Running Torque:

48.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Power Dissipation Rating Per Section In Watts:

100.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-22/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0