NSN 5905-00-064-1230

Precision Wire Wound Variable Resistor - Page 1 of 2



-1230

View Online at https://aerobasegroup.com/nsn/5905-00-064-
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.9360 inches and 1.9370 inches
Pilot Length:
Between 0.0290 inches and 0.0320 inches
Overall Length:
Between 1.217 inches and 1.260 inches
Undercut Diameter:
Between 1.9375 inches and 1.9385 inches
Undercut Width:
Between 0.0700 inches and 0.0900 inches
Body Diameter:
Between 1.990 inches and 2.010 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.198 inches and 0.218 inches
Body Length:
Between 0.990 inches and 1.010 inches
Overall Diameter:
Between 2.099 inches and 2.151 inches
Mounting Lip Diameter:
Between 1.9900 inches and 2.0100 inches
Mounting Lip Depth:
Between 0.0680 inches and 0.0850 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 319.0 and 321.0
Maximum Starting Torque:
0.60 inch-ounces
Shaft End Play:

Shaft End Play:

0.006 inches

NSN 5905-00-064-1230

No **Fiig:**

Precision Wire Wound Variable Resistor - Page 2 of 2



Lateral Runout:	
0.001 inches	
Pilot Diameter Runout:	
0.001 inches	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
500.0 ohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
105.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-30.0/+30.0 single section	
Power Dissipation Rating Per Section In Watts:	
4.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-1.0 to 1.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Test Data Document:	
81349-mil-r-8903 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
12 solder stud	
Specification Data:	
81349-mil-r-8903 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	