

View Online at <https://aerobasegroup.com/nsn/5905-00-064-4612>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9680 inches

Pilot Length:

0.0620 inches

Overall Length:

0.747 inches

Undercut Diameter:

1.062 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.125 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.625 inches

Body Length:

0.605 inches

Overall Diameter:

1.125 inches

Mounting Lip Diameter:

1.1250 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

350.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-0.5 to 0.5 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

65.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0