## NSN 5905-00-064-8942

**Section Quantity:** 

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-064-8942

Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.957 inches
Body Diameter:
1.680 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 1.453 inches and 1.547 inches
Mounting Bushing Length:
Between 0.328 inches and 0.422 inches
Body Length:
1.410 inches
Overall Diameter:
2.260 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
40.00 inch-ounces
Maximum Stop Torque:
240.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
Between 0.485 inches and 0.515 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing

## NSN 5905-00-064-8942

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
25.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/3 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No.

Fiig:

A002a0