## NSN 5905-00-064-9215

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-064-9215 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.625 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.187 inches **Mounting Bushing Length:** 0.187 inches **Body Length:** 1.125 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

500.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

## NSN 5905-00-064-9215

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No