NSN 5905-00-065-0128

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-065-0128

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Pilot Diameter:
1.87500 inches
Pilot Length:
0.06200 inches
Overall Length:
1.812 inches
Undercut Diameter:
1.687 inches
Undercut Width:
0.15600 inches
Body Diameter:
1.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.727 inches
Body Length:
1.000 inches
Overall Diameter:
2.031 inches
Mounting Lip Diameter:
2.00000 inches
Mounting Lip Depth:
0.09300 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
358.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0

NSN 5905-00-065-0128

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Fixed Tap Quantity Per Section:** 2 single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No