Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-066-4093

Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

Reliability Indicator:

Not established

Body Diameter:

0.710 inches

Mounting Hole Diameter:

0.088 inches

Shaft Diameter:

0.125 inches

Shaft Length:

4.438 inches

Body Length:

0.380 inches

Shaft Style:

Round

Switch Type:

Rotary

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Lateral Distance Between Mounting Hole Centers:

1.030 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

375.0 ohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

1.0 free air single section



Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section **Actuator Travel Control Feature:** Continuous motion Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0