NSN 5905-00-067-6472

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-067-6472

| View Online at https://aerobasegroup.com/nsn/5905-00-067-6472 | |
|---|----------|
| Section Quantity: | |
| 1 | |
| Body Style: | |
| Rectangular w/mounting holes/slots | |
| Reliability Indicator: | |
| Not established | |
| Mounting Hole Diameter: | |
| Between 0.088 inches and 0.098 inches | |
| Shaft Diameter: | |
| Between 0.100 inches and 0.130 inches | |
| Shaft Length: | |
| Between 0.060 inches and 0.080 inches | |
| Body Length: | |
| Between 1.218 inches and 1.282 inches | |
| Body Width: | |
| Between 0.250 inches and 0.300 inches | |
| Body Height: | |
| 0.312 inches | |
| Shaft Style: | |
| Round, slotted | |
| Contact Arm Electrical Off Position: | |
| Fully ccw | |
| Actuator Type: | |
| Single shaft | |
| Effective Electrical Rotation In Deg Angular Rotation: | |
| Between 6120.0 and 9720.0 | |
| Lateral Distance Between Mounting Hole Centers: | |
| Between 0.995 inches and 1.005 inches | |
| Mounting Facility Quantity: | |
| 2 | |
| Terminal Location: | |
| Rear end | |
| Mounting Method: | |
| Unthreaded hole | |
| Electrical Resistance Per Section: | |
| 5.000 kilohms single section | |
| Rotary Actuator Travel In Angular Deg: | |
| Between 6120.0 and 9720.0 | |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rate | d Power: |
| 150.0 single section | |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Ce | lsius: |
| | |

-50.0 to 50.0 single section

NSN 5905-00-067-6472

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts: |
|--|
| 0.7 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0 to 5.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 wire lead |
| Specification Data: |
| 81349-mil-r-27208/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No. |