NSN 5905-00-068-6013

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-068-6013 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: Between 0.0600 inches and 0.0800 inches **Overall Length:** 2.000 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0600 inches

Body Diameter: 2.000 inches **Shaft Diameter:** 0.250 inches

Shaft Length: 0.750 inches **Body Length:**

1.250 inches

Overall Diameter: 2.000 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style: Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

NSN 5905-00-068-6013

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
4.00 inch-ounces
Shaft End Play:
0.003 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.2
Terminal Location:
Upper adjacent side two rows
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Special Features:
A w/two wingresistors one ea end of resistor element
Test Data Document:
81413-170205-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
5 solder stud
Shelf Life:

N/a

NSN 5905-00-068-6013

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0