NSN 5905-00-068-6641

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-068-6641

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.300 inches and 1.340 inches
Terminal Length:
11.500 inches
Overall Height:
Between 0.310 inches and 0.330 inches
Overall Width:
Between 0.180 inches and 0.200 inches
Mounting Hole Diameter:
Between 0.088 inches and 0.098 inches
Shaft Diameter:
Between 0.105 inches and 0.115 inches
Shaft Length:
Between 0.060 inches and 0.080 inches
Body Length:
Between 1.240 inches and 1.260 inches
Body Width:
Between 0.175 inches and 0.185 inches
Body Height:
Between 0.310 inches and 0.330 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:

5.000 kilohms single section

NSN 5905-00-068-6641

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: Between 7918.0 and 7922.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**