## NSN 5905-00-069-4992

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-069-4992

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.8750 inches
Pilot Length:
0.0710 inches
Overall Length:
1.625 inches
Undercut Diameter:
1.062 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.688 inches
Body Length:
1.000 inches
Overall Diameter:
1.437 inches
Mounting Lip Diameter:
1.1250 inches
Mounting Lip Depth:
Between 0.0540 inches and 0.0620 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
354.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:

0.60 inch-ounces

## NSN 5905-00-069-4992

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.0025 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-00-069-4992

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0