NSN 5905-00-070-4805

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-070-4805 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 2.87400 inches and 2.87500 inches Pilot Length: 0.06200 inches **Overall Length:** 3.020 inches **Undercut Diameter:** 2.875 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 3.020 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.840 inches **Body Length:** 2.180 inches **Mounting Lip Diameter:** Between 2.99000 inches and 3.0100 inches **Mounting Lip Depth:** 0.07800 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft

Electrical Resistance Per Section: 2.500 kilohms 2nd section

Power Dissipation Rating Per Section In Watts:

1.0 free air 3rd section

NSN 5905-00-070-4805

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Q	esistance	Tolerance	Per Section	In P	ercent.
7	esisiance	i olei alice	rei Section	шг	ercent.

-1.0 to 1.0 2nd section

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0