## NSN 5905-00-070-6037

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-070-6037

Section Quantity:
3
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.249 inches
Shaft Length:
0.687 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.953 inches
Body Width:
1.281 inches
Body Height:
1.062 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
700.0 ohms all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

## NSN 5905-00-070-6037

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	In	Percent:
Nesistance	I Olei allee		Section		i Cicciii.

-10.0 to 10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

**Standard Taper Curve Per Section:** 

A all sections

**Terminal Type And Quantity:** 

9 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0