Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-070-8062

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

**Overall Length:** 

0.578 inches

#### Body Diameter:

0.798 inches

Shaft Diameter:

0.156 inches

Shaft Length:

0.125 inches

### Body Length:

0.375 inches

#### **Overall Diameter:**

1.312 inches

Shaft Style:

Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.360 inches

#### Fragility Factor:

Moderately delicate

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Tab

#### **Electrical Resistance Per Section:**

1.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

300.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

## Power Dissipation Rating Per Section In Watts:

0.3 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

#### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0