

View Online at <https://aerobasegroup.com/nsn/5905-00-070-8063>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

0.375 inches

**Flat Height:**

0.156 inches

**Body Diameter:**

1.109 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.813 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

0.875 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.438 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

15.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0 to 20.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

65.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0