## NSN 5905-00-070-9568

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-070-9568 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.87500 inches Pilot Length: 0.06200 inches **Overall Length:** 2.350 inches **Undercut Diameter:** 1.870 inches **Undercut Width:** 0.07800 inches **Body Diameter:** 2.109 inches **Angle Of Mounting Hole In Deg:** 35.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Body Length:** 1.412 inches **Overall Diameter:** 2.594 inches **Mounting Lip Diameter:** 2.00000 inches **Mounting Lip Depth:** 0.09300 inches **Mounting Hole/stud Circle Diameter:** 0.625 inches **Shaft Style:** Round **Actuator Type:** Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

## NSN 5905-00-070-9568

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Starting Torque:
6.00 inch-ounces
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring and threaded hole
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-0.015/+0.015 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-15.0 to 15.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:

N/a

## NSN 5905-00-070-9568

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0