

View Online at https://aerobasegroup.com/nsn/5905-00-071-9921

# Section Quantity:

1

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

# **Pilot Diameter:**

1.8750 inches

#### **Pilot Length:**

0.0620 inches

## **Undercut Diameter:**

1.812 inches

# **Undercut Width:**

0.0730 inches

### **Body Diameter:**

# 2.000 inches

Angle Of Mounting Hole In Deg:

60.0

# Angle Between Centerlines Of Mounting Holes In Deg:

120.0

# Shaft Diameter:

0.250 inches

## Shaft Length:

0.645 inches

#### **Body Length:**

2.125 inches

# Mounting Lip Diameter:

2.0000 inches

# Mounting Lip Depth:

0.0930 inches

# Mounting Hole/stud Circle Diameter:

1.250 inches

#### Shaft Style:

Round

# Shaft Bearing Type:

Ball

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

3600.0

# Maximum Starting Torque:

1.30 inch-ounces



## Maximum Running Torque:

0.90 inch-ounces

#### Maximum Stop Torque:

600.00 inch-ounces

# Shaft End Play:

0.005 inches

#### Shaft Runout:

0.0005 inches

#### Lateral Runout:

0.0015 inches

#### **Pilot Diameter Runout:**

0.0001 inches

#### Shaft Radial Play:

0.001 inches

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Servo mount

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

3780.0

#### **Function Conformity Tolerance Per Section:**

-0.15/+0.15 single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

## **Function Conformity Per Section:**

Single section independent linearity

## **Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 single section

#### **Actuator Travel Control Feature:**

Stops

## **Function Characteristic Per Section:**

Single section linear

#### Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## **Terminal Type And Quantity:**

3 tab, solder lug

## Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0