NSN 5905-00-072-3091

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-072-3091

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.9683 inches and 0.9688 inches
Pilot Length:
0.0620 inches
First Flat Length:
0.394 inches
Flat Height:
Between 0.104 inches and 0.106 inches
Undercut Diameter:
0.969 inches
Undercut Width:
0.0570 inches
Body Diameter:
1.062 inches
Shaft Diameter:
Between 0.1242 inches and 0.1247 inches
Shaft Length:
Between 0.594 inches and 0.656 inches
Body Length:
0.680 inches
Mounting Lip Diameter:
1.0620 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
0.35 inch-ounces
Maximum Running Torque:
0.35 inch-ounces
Fragility Factor:

Moderately rugged

NSN 5905-00-072-3091

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
320.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Test Data Document:
97942-577r900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0