## NSN 5905-00-072-7042

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-072-7042 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Diameter:** 2.750 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.438 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 3.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.375 inches **Center To Center Distance Between Terminals:** 0.100 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

32.0

Terminal Location:
Rear end

Mounting Method:
Standard bushing

Electrical Resistance Per Section:
50.0 ohms single section

## NSN 5905-00-072-7042

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
350.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
0.200 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
50.0 to 50.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Resistance Tolerance Per Section In Percent:	
2.0 to 2.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
55.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A002a0	