Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-072-8045

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## Reliability Indicator:

Not established

#### **Overall Length:**

1.078 inches

#### **Body Diameter:**

0.531 inches

#### Shaft Diameter:

0.126 inches

Shaft Length:

0.375 inches

#### Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.469 inches

#### Overall Diameter:

0.531 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 10'30 oclock

### Nonturn Device Radius:

0.485 inches

### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Locking bushing

## **Electrical Resistance Per Section:**

1.0 megohms single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section



Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0