NSN 5905-00-072-8518

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-072-8518

Section Quantity:
1
Body Style:
Cylindrical tab/flange mounted
Reliability Indicator:
Not established
Overall Length:
7.703 inches
Body Diameter:
0.718 inches
Mounting Hole Diameter:
0.136 inches
Shaft Diameter:
0.250 inches
Shaft Length:
7.312 inches
Body Length:
0.391 inches
Overall Diameter:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Fragility Factor:
Moderately rugged
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
680.0 ohms single section
Rotary Actuator Travel In Angular Deg:

270.0

NSN 5905-00-072-8518

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -15.0 to 15.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No