NSN 5905-00-073-7922

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-073-7922

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
2.87500 inches
Pilot Length:
0.03120 inches
Overall Length:
2.000 inches
Undercut Diameter:
2.000 inches
Undercut Width:
1.68750 inches
Body Diameter:
3.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.250 inches
Overall Diameter:
3.000 inches
Mounting Lip Diameter:
3.00000 inches
Mounting Lip Depth:
0.09370 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
15.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-00-073-7922

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: