

View Online at https://aerobasegroup.com/nsn/5905-00-073-8693

# Section Quantity:

2

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

## **Pilot Diameter:**

0.6250 inches

#### **Pilot Length:**

0.0620 inches

## **Undercut Diameter:**

0.625 inches

## **Undercut Width:**

0.0620 inches

### **Body Diameter:**

## 0.875 inches

## Angle Of Mounting Hole In Deg:

90.0

## Angle Between Centerlines Of Mounting Holes In Deg:

120.0

# Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

# Shaft Length:

0.312 inches

## **Body Length:**

2.995 inches

## Mounting Lip Diameter:

0.8750 inches

## Mounting Lip Depth:

0.0620 inches

## Mounting Hole/stud Circle Diameter:

0.750 inches

#### Shaft Style:

Round, slotted

## Shaft Bearing Type:

Ball

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

3600.0

# Maximum Starting Torque:

1.20 inch-ounces



### Maximum Running Torque:

1.00 inch-ounces

### Maximum Stop Torque:

128.00 inch-ounces

## Shaft End Play:

0.004 inches

#### Shaft Runout:

0.001 inches

### Lateral Runout:

0.003 inches

#### **Pilot Diameter Runout:**

0.0015 inches

#### Shaft Radial Play:

0.002 inches

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Clamp ring

### **Electrical Resistance Per Section:**

1.0 kilohms all sections

#### Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

2666.0 all sections

# Rotary Actuator Travel In Angular Deg:

3600.0

### **Function Conformity Tolerance Per Section:**

-0.15/+0.15 all sections

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

### **Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

#### **Function Conformity Per Section:**

All sections absolute linearity

#### **Fixed Tap Quantity Per Section:**

1 all sections

## **Tap Location Tolerance Per Section:**

-2.0 to 2.0 degrees angular rotation all sections

## **Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 all sections

### **Actuator Travel Control Feature:**

Clutch

#### **Function Characteristic Per Section:**

All sections linear

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections



Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0