## NSN 5905-00-073-8993

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-073-8993 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0300 inches Pilot Length: 0.0450 inches **Undercut Diameter:** 1.030 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.109 inches **Angle Of Mounting Hole In Deg:** 30.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 0.120 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.275 inches **Body Length:** 0.635 inches **Mounting Lip Diameter:** 1.1090 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 0.625 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0

**End Application:** 

ARMA-ME-NTS-UBSY

## NSN 5905-00-073-8993

No Fiig:

Precision Nonwire Wound Variable Resistor - Page 2 of 2



| Screw Thread Diameter:   |
|--|
| 0.112 inches   |
| Screw Thread Series Designator:  |
| Jnc  |
| Screw Thready Qty Per Inch (tpi):  |
| 40.0   |
| Mounting Facility Quantity:  |
| 3  |
| Terminal Location:   |
| Lower adjacent side single row   |
| Mounting Method:   |
| Threaded hole  |
| Rotary Actuator Travel In Angular Deg:   |
| 360.0  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 230.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 20.0 free air single section   |
| Function Conformity Per Section:   |
| Single section absolute linearity  |
| Fixed Tap Quantity Per Section:  |
| 1 single section   |
| Resistance Tolerance Per Section In Percent:   |
| 10.0/+10.0 single section  |
| Actuator Travel Control Feature:   |
| Continuous motion  |
| Tap Location From Ccw Terminal Per Section In Ohms:  |
| 500.0 single section   |
| Function Characteristic Per Section:   |
| Single section linear  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  |
| 70.0 single section  |
| Special Features:  |
| Consists of ring-1, p/n ms16624-1031; gear-1, p/n 11011251; spring-1, p/n 11011252; gearshaft-1, p/n 11011254; pin-1, p/n          |
| ms39086-100; screw-3, p/n ms35275-212; washer-1, p/n ms15795-804; wire-ar, p/n ms20995c20; resistor-1, p/n 8445009; adapter-1, p/n |
| 11011253   |
| Terminal Type And Quantity:  |
| 3 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |