NSN 5905-00-073-8993

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-073-8993 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0300 inches Pilot Length: 0.0450 inches **Undercut Diameter:** 1.030 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.109 inches **Angle Of Mounting Hole In Deg:** 30.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 0.120 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.275 inches **Body Length:** 0.635 inches **Mounting Lip Diameter:** 1.1090 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 0.625 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0

End Application:

ARMA-ME-NTS-UBSY

NSN 5905-00-073-8993

No Fiig:

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Jnc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
3
Terminal Location:
Lower adjacent side single row
Mounting Method:
Threaded hole
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
230.0 single section
Power Dissipation Rating Per Section In Watts:
20.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
500.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Special Features:
Consists of ring-1, p/n ms16624-1031; gear-1, p/n 11011251; spring-1, p/n 11011252; gearshaft-1, p/n 11011254; pin-1, p/n
ms39086-100; screw-3, p/n ms35275-212; washer-1, p/n ms15795-804; wire-ar, p/n ms20995c20; resistor-1, p/n 8445009; adapter-1, p/n
11011253
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization: