## NSN 5905-00-074-4395

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-074-4395

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.625 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.313 inches
Mounting Bushing Length:
0.188 inches
Body Length:
1.156 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125 0 single section

125.0 single section

## NSN 5905-00-074-4395

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** Demilitarization: No