## NSN 5905-00-074-4418

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-074-4418 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.687 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.125 inches

**Mounting Bushing Length:** 

0.375 inches

**Body Length:** 

1.187 inches

**Shaft Style:** 

Round, slotted

**Actuator Type:** 

Single shaft

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

0.531 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

10.000 kilohms 2nd section

**Power Dissipation Rating Per Section In Watts:** 

1.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 2nd section

## NSN 5905-00-074-4418

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0