NSN 5905-00-075-0511

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-075-0511 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.9683 inches and 0.9688 inches Pilot Length: 0.0620 inches **Overall Length:** 2.138 inches **Undercut Diameter:** Between 0.970 inches and 0.980 inches **Undercut Width:** 0.0600 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** Between 0.1195 inches and 0.120 inches **Shaft Length:** 0.500 inches **Body Length:** 1.700 inches **Overall Diameter:** 1.156 inches **Mounting Lip Diameter:** Between 1.0570 inches and 1.0670 inches **Mounting Lip Depth:** 0.0600 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:**

2.00 inch-ounces

Shaft End Play:

0.002 inches

NSN 5905-00-075-0511



Precision Wire Wound Variable Resistor - Page 2 of 3
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.0006 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
4.0 kilohms 3rd section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20 to 0.20 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-300.0/+300.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

400.0 all sections

Function Characteristic Per Section:

All sections linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

12 solder stud

Shelf Life:

N/a

NSN 5905-00-075-0511

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0