NSN 5905-00-075-1982

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-075-1982
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.8750 inches
Pilot Length:
0.0620 inches
Overall Length:
3.370 inches
Undercut Diameter:
1.875 inches
Undercut Width:
0.0620 inches
Body Diameter:
2.000 inches
Angle Of Mounting Hole In Deg:
90.0
Angle Between Centerlines Of Mounting Holes In Deg:
120.0
Shaft Diameter:
0.250 inches
Shaft Length:
0.870 inches
Body Length:
1.000 inches
Overall Diameter:
2.500 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0620 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball

Actuator Type:

Double ended shaft

NSN 5905-00-075-1982

Effective Electrical Rotation In Deg Angular Rotation:

Precision Wire Wound Variable Resistor - Page 2 of 3



315.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.0015 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-130.0 to 130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

3 turret

40.0 single section

Terminal Type And Quantity:

NSN 5905-00-075-1982

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0