Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-075-6838

Section	Quantity:

1

- Body Style: Rectangular w/mounting holes
- Reliability Indicator:
- Not established
- **Terminal Length:**
- 0.172 inches
- Mounting Hole Diameter:
- 0.078 inches
- Shaft Diameter:
- 0.083 inches
- Shaft Length:
- 0.030 inches
- Body Length:
- 0.538 inches
- **Body Width:**
- 0.219 inches
- Body Height:
- 0.500 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 9000.0
- Center To Center Distance Between Terminals:
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.520 inches
- Mounting Facility Quantity:
- 2
- Terminal Location: Lower adjacent side single row Mounting Method: Unthreaded hole Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg:
- 9000.0



Center To Center Distance Between Center Terminal And Outside Terminal:	
0.100 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
175.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-50.0 to 50.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0 to 5.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	