NSN 5905-00-075-8103

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-075-8103

| • |
|--|
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| Between 0.380 inches and 0.435 inches |
| Terminal Length: |
| Between 0.288 inches and 0.315 inches |
| Overall Height: |
| Between 0.390 inches and 0.440 inches |
| Overall Width: |
| Between 0.187 inches and 0.219 inches |
| Shaft Diameter: |
| Between 0.080 inches and 0.100 inches |
| Shaft Length: |
| Between 0.030 inches and 0.050 inches |
| Body Length: |
| Between 0.360 inches and 0.390 inches |
| Body Width: |
| Between 0.187 inches and 0.219 inches |
| Body Height: |
| Between 0.360 inches and 0.390 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 9000.0 |
| Center To Center Distance Between Terminals: |
| Between 0.190 inches and 0.210 inches |
| Fragility Factor: |
| Moderately rugged |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Terminal |
| Features Provided: |
| Humidity proof |
| Electrical Resistance Per Section: |
| 50.0 ohms single section |
| |

NSN 5905-00-075-8103 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator Travel In Angular Deg: |
|---|
| 9000.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| Between 0.090 inches and 0.110 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 175.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| 50.0 to 50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| 5.0 to 5.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| 4002a0 |
| |