NSN 5905-00-076-4292

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-076-4292 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7000 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.880 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 135.0 **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.606 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 0.780 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:**

350.0 **Maximum Starting Torque:** 0.10 inch-ounces **Maximum Running Torque:**

0.10 inch-ounces

NSN 5905-00-076-4292

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.003 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
,
125.0 single section
125.0 single section
125.0 single section Power Dissipation Rating Per Section In Watts:
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section:
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature:
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features:
Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Three no.8-80 nf screws to be supplied, 228 additional length, pot shall remain assembled when screws are removed
125.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0 to 3.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Three no.8-80 nf screws to be supplied, 228 additional length, pot shall remain assembled when screws are removed Terminal Type And Quantity:

NSN 5905-00-076-4292

Precision Wire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0