NSN 5905-00-076-5749

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-076-5749 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.203 inches **Overall Height:** Between 0.370 inches and 0.380 inches **Shaft Diameter:** Between 0.088 inches and 0.098 inches **Shaft Length:** Between 0.075 inches and 0.085 inches **Body Length:** Between 0.397 inches and 0.413 inches **Body Width:** Between 0.185 inches and 0.195 inches **Body Height:** Between 0.370 inches and 0.380 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:**

9000.0

NSN 5905-00-076-5749

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**