NSN 5905-00-077-8515

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-077-8515

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
1.234 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.375 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.703 inches
Overall Diameter:
1.281 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
300.0 Nonturn Device Location:
Nonturn Device Location:
Nonturn Device Location: At 9 oclock
Nonturn Device Location: At 9 oclock Nonturn Device Radius:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section: 5.000 kilohms single section
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Locking bushing Electrical Resistance Per Section:

2.0 free air single section

NSN 5905-00-077-8515

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Standard Taper Curve Per Section: C single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A002a0