NSN 5905-00-078-8068

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-078-8068 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.625 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.875 inches **Overall Diameter:** 1.625 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Starting Torque:** 2.00 inch-ounces **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 kilohms single section

Power Dissipation Rating Per Section In Watts: 3.0 free air single section

NSN 5905-00-078-8068

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	In	Percent:

-2.0/+2.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0