NSN 5905-00-078-8120

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-078-8120 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.870 inches **Body Diameter:** 0.560 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.810 inches **Mounting Bushing Length:** 0.232 inches **Body Length:** 1.060 inches **Overall Diameter:** 0.560 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Maximum Stop Torque:** 15.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:**

0.002 inches

0.003 inches

Shaft Radial Play:

NSN 5905-00-078-8120

Mechanical Backlash In Deg Angular Rotation:

Precision Wire Wound Variable Resistor - Page 2 of 3



1.5 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 10.0 kilohms single section Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 1800.0 single section **Rotary Actuator Travel In Angular Deg:** 3620.0 **Function Conformity Tolerance Per Section:** -0.20/+0.20 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section **Power Dissipation Rating Per Section In Watts:** 2.5 free air single section **Function Conformity Per Section:** Single section terminal base linearity **Fixed Tap Quantity Per Section:** 1 single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops **Tap Location From Ccw Terminal Per Section In Ohms:** 5000.0 single section

Terminal Type And Quantity:

Function Characteristic Per Section:

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

4 tab, solder lug

Single section linear

40.0 single section

NSN 5905-00-078-8120

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	Life:
-------	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0