Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-078-9475

Section	Quantity:

1

- Body Style: Rectangular w/mounting holes
- Reliability Indicator:
- Not established
- **Terminal Length:**
- 0.188 inches
- Mounting Hole Diameter:
- 0.075 inches
- Shaft Diameter:
- 0.060 inches
- Shaft Length:
- 0.154 inches
- Body Length:
- 0.405 inches
- **Body Width:**
- 0.184 inches
- Body Height:
- 0.375 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 360.0
- Center To Center Distance Between Terminals:
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.375 inches
- Mounting Facility Quantity:
- 2
- Terminal Location: Left adjacent side two rows
- Mounting Method:
- Terminal and unthreaded hole
- Center To Center Distance Between Terminal Rows:
- 0.100 inches
- **Electrical Resistance Per Section:**
- 100.0 ohms single section
- **Rotary Actuator Travel In Angular Deg:**
- 360.0



Center To Center Distance Between Center Terminal And Outside Terminal:	
0.100 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-50.0 to 50.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0 to 5.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
50.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A002a0	