

View Online at <https://aerobasegroup.com/nsn/5905-00-079-1617>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.063 inches

First Flat Length:

0.437 inches

Flat Height:

0.125 inches

Body Diameter:

0.938 inches

Shaft Diameter:

0.265 inches

Shaft Length:

1.188 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.875 inches

Overall Diameter:

1.203 inches

Undercut Diameter:

0.187 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Undercut Length:

0.594 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms 1st section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 all sections

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

F all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0