NSN 5905-00-079-2959

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-079-2959 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.000 inches **Body Length:** 0.500 inches **Mounting Hole/stud Circle Diameter:** 0.625 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 3.52 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 7.0 free air single section **Fixed Tap Quantity Per Section:** 3 single section

-2.0 to 2.0 ohms single section

Tap Location Tolerance Per Section:

NSN 5905-00-079-2959

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 single section

Tap Location From Ccw Terminal Per Section In Ohms:

3272.0 3rd section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0