

View Online at <https://aerobasegroup.com/nsn/5905-00-079-6362>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Overall Length:**

0.766 inches

**Body Diameter:**

Between 0.769 inches and 0.801 inches

**Body Length:**

0.422 inches

**Overall Diameter:**

Between 0.808 inches and 0.812 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

200.0

**Maximum Starting Torque:**

10.00 inch-ounces

**Nonturn Device Location:**

At 6 oclock or at 9 oclock

**Nonturn Device Radius:**

0.370 inches

**Terminal Location:**

Rear end

**Mounting Method:**

Flange

**Features Provided:**

Grounded contact arm and nonmetallic shaft

**Electrical Resistance Per Section:**

10.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

240.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0