

View Online at <https://aerobasegroup.com/nsn/5905-00-079-8634>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.8740 inches and 1.8750 inches

**Pilot Length:**

0.0630 inches

**Overall Length:**

1.500 inches

**Undercut Diameter:**

Between 1.874 inches and 1.875 inches

**Undercut Width:**

Between 0.0550 inches and 0.0850 inches

**Body Diameter:**

2.000 inches

**Shaft Diameter:**

Between 0.249 inches and 0.250 inches

**Shaft Length:**

0.437 inches

**Body Length:**

1.000 inches

**Overall Diameter:**

2.218 inches

**Mounting Lip Diameter:**

2.0000 inches

**Mounting Lip Depth:**

0.0880 mils and 0.0980 centimeters

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Cubic Measure:**

3.141 cubic inches

**Electrical Resistance Per Section:**

2.5 percent, rated amperes c and better flooring

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-400.0/+400.0 single section

**Function Conformity Per Section:**

Single section absolute conformity

**Fixed Tap Quantity Per Section:**

1 single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Tap Location From Ccw Terminal Per Section In Ohms:**

1250.0 single section

**Function Characteristic Per Section:**

7 oclock primary input

**Special Features:**

Coupling attached to shaft

**Test Data Document:**

18876-13059259 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0