NSN 5905-00-079-9913

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-079-9913 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.3750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.641 inches **Undercut Diameter:** 0.375 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.540 inches **Shaft Diameter:** 0.0935 inches **Shaft Length:** 0.313 inches **Body Length:** 1.141 inches **Overall Diameter:** 0.540 inches **Mounting Lip Diameter:** 0.5400 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0

Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.50 inch-ounces

NSN 5905-00-079-9913

Shaft End Play: 0.0045 inches

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:						
0.002 inches						
Lateral Runout:						
0.002 inches						
Pilot Diameter Runout:						
0.0015 inches						
Shaft Radial Play:						
0.002 inches						
Fragility Factor:						
Moderately rugged						
Terminal Location:						
Rear end						
Mounting Method:						
Clamp ring						
Features Provided:						
Humidity proof						
Electrical Resistance Per Section:						
2.0 percent, rated amperes c and better flooring						
Rotary Actuator Travel In Angular Deg:						
3630.0						
Function Conformity Tolerance Per Section:						
-0.50/+0.50 single section						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
140.0 single section						
Power Dissipation Rating Per Section In Watts:						
2.5 7th secondary quality						
Function Conformity Per Section:						
Single section independent linearity						
Resistance Tolerance Per Section In Percent:						
-5.0/+5.0 single section						
Actuator Travel Control Feature:						
Clutch						
Function Characteristic Per Section:						
7 oclock all primaries						
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:						
-20.0/+20.0 single section						
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:						
40.0 single section						
Terminal Type And Quantity:						
3 tab, solder lug						
Shelf Life:						
N/a						

NSN 5905-00-079-9913

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A002a0