NSN 5905-00-079-9939

Fiig: A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-079-9939

20.0 to 20.0 to 20.0 Electrical Resistance:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 1.870 kilohms Resistance Tolerance in Percent: -1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.19 inches and 0.281 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.48 inches and 0.562 inches Power Dissipation Rating in Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Avait terminal each end Test Data Document: 814349-mili-795 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directorius, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: Na Unit Of Measure:	
1.870 kilohms Resistance Tolerance In Percent: -1.000/41.000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Diameter: Between 0.219 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-795 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-793/13 government specification Shelf Life: Na Unit of Measure: - Cubic Indeasure: - Cubi	
Resistance Tolerance In Percent: -1,000/-1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -45.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,875 inches and 2,125 inches Body Diameter: Between 0,219 inches and 0,281 inches Body Length: Between 0,219 inches and 0,562 inches Power Dissipation Rating In Watts: 0,150 free air Cubic Measure (non-core): 0,035 cubic inches Style Designator: Avial terminal each end 181349-mill-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications. reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-93/13 government specification Shelf Life: Na Unit Of Measure: - Demilitarization:	
1.000/4.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating in Watts: 0.150 free air Cubic Measure (non-core): 0.335 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil93/13 government specification Shelf Life: Na Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: -Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -Between 1.875 inches and 2.125 inches -Body Jameter: -Between 0.219 inches and 0.281 inches -Body Length: -Between 0.438 inches and 0.562 inches -Power Dissipation Rating In Watts: -0.150 free air -Cubic Measure (non-core): -0.035 cubic inches -Style Designator: -Axial terminal each end -Test Data Document: -B149-mil93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.)Specification Data: -B149-mil93/13 government specification -Shelf Life: -Na -Unit Of Measure:	
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Body Length: Between 0.438 inches and 0.562 inches Coulie Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mill93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil93/13 government specification Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Jameter: Between 0.219 inches and 0.281 inches Body Jameter: Between 0.219 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: Via Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -6.5.0 to 14.5.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Diameter: Between 0.219 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-milk-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-milk-93/13 government specification Shelf Life: Via Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.438 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
-6.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 1.875 inches and 0.281 inches Body Diameter: Between 0.438 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mill93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-93/13 government specification Shelf Life: Na Unit Of Measure: Demilitarization:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: Na Unit Of Measure: Demilitarization:	
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.876 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating in Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure:	
Reliability Indicator: Not established Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure:	
Note stablished Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure:	
Terminal Length: Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure:	
Between 1.875 inches and 2.125 inches Body Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure:	
Bedy Diameter: Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure:	-
Between 0.219 inches and 0.281 inches Body Length: Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Between 0.438 inches and 0.562 inches Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Power Dissipation Rating In Watts: 0.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
O.150 free air Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Cubic Measure (non-core): 0.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
O.035 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Axial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Specification Data: 81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
81349-mil-r-93/13 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	81349-mil-r-93/13 government specification
Unit Of Measure: Demilitarization:	
Demilitarization:	N/a
Demilitarization:	
	
	Demilitarization:
	No