## NSN 5905-00-080-2908

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-080-2908



**Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.215 inches **Overall Height:** Between 0.302 inches and 0.322 inches **Overall Width:** Between 0.200 inches and 0.220 inches **Mounting Hole Diameter:** Between 0.076 inches and 0.096 inches **Shaft Diameter:** Between 0.070 inches and 0.090 inches **Shaft Length:** Between 0.065 inches and 0.085 inches **Body Length:** Between 1.130 inches and 1.150 inches **Body Width:** Between 0.200 inches and 0.220 inches **Body Height:** Between 0.302 inches and 0.322 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** Between 0.990 inches and 1.010 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 5.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 200.0 single section

## NSN 5905-00-080-2908

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0