NSN 5905-00-080-3218

Fiig: A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-080-3218

-400.0 to 400.0 Electrical Resistance: 4,700 ohms Resistance Tolerance In Percent: -5,000 to 5,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350,0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55,0 to 350,0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Longth: Between 1,375 inches and 2,125 inches Body Diameter: Between 0,125 inches and 0,251 inches Body Diameter: Between 0,125 inches and 0,583 inches Power Dissipation Rating in Watts: 3,000 free air Cubic Measure (non-core): 0,028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mill-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-2644 government specification Sheft Life: Na Unit Of Measure: Demilitarization:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 4,700 ohms Resistance Tolerance in Percent: 5,000 to 5,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35,00 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55,01 to 35,00 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55,01 to 35,00 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: Between 1,375 inches and 2,125 inches Body Diameter: Between 0,1375 inches and 0,251 inches Body Diameter: Between 0,437 inches and 0,563 inches Power Dissipation Rating in Watts: 3,000 free air Cubic Measure (non-core): 0,225 cubic inches Style Designatior: Axial terminal each end Test Data Document: 81349-mil+-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+-26/4 government specification Sheff Life: N/a Unit of Measure:	
4.700 ohms Resistance Tolerance in Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 1.375 inches and 0.251 inches Body Diameter: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.28 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mili-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-264 government specification Shelf Life: N/a Unit Of Measure: -	
Resistance Tolerance in Percent: -5.000 to 5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating in Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil+-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+-26/4 government specification Sheff Lite: Na Unit Of Measure: -	
-5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Batween 1.375 inches and 2.125 inches Body Dlameter: Between 0.137 inches and 0.251 inches Body Length: Between 0.137 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 acubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r.26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r.264 government specification Sheff Lite: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r268 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r2644 government specification Shelf Life: N/A Unit Of Measure:	
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Diameter: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mili-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-2649 government specification Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Jameter: Between 0.125 inches and 0.251 inches Body Jameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.427 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mili-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-2649 government specification Shelf Life: Na Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Diameter: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-milr-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-264 government specification Na Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 2.25 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-milt-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milt-26/4 government specification Na Unit Of Measure:	
-5.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-28/4 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Not established Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Terminal Length: Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Between 1.375 inches and 2.125 inches Body Diameter: Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	-
Between 0.125 inches and 0.251 inches Body Length: Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Between 0.437 inches and 0.563 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
3.000 free air Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Cubic Measure (non-core): 0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
0.028 cubic inches Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Axial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Specification Data: 81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
81349-mil-r-26/4 government specification Shelf Life: N/a Unit Of Measure:	
Shelf Life: N/a Unit Of Measure:	81349-mil-r-26/4 government specification
Unit Of Measure:	
	N/a
Demilitarization:	
	Demilitarization:
No	