NSN 5905-00-080-3663



View Online	e at https://aerobasegroup.com/nsn/5905-00-080-3663
Section Qu	uantity:
1	
Body Style	:
Cylindrical	bushing mounted
Reliability	Indicator:
Not establis	shed
Overall Le	ngth:
Between 1.	312 inches and 1.656 inches
Body Dian	neter:
Between 1.	032 inches and 1.156 inches
Shaft Dian	neter:
Between 0.	248 inches and 0.251 inches
Shaft Leng	pth:
Between 0.	844 inches and 0.906 inches
Mounting	Bushing Length:
Between 0.	360 inches and 0.432 inches
Body Leng	pth:
Between 0.	468 inches and 0.750 inches
Overall Dia	ameter:
1.515 inche	es
Shaft Style	::
Round, slo	tted
Actuator T	уре:
Single shaf	t
Maximum	Starting Torque:
6.00 inch-o	unces
Maximum	Stop Torque:
128.00 inch	n-ounces

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Fiig: A002a0

NSN 5905-00-080-3663 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No