NSN 5905-00-080-3892

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-080-3892

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:						
-170.0 to 170.0						
Electrical Resistance:						
12.000 ohms						
Resistance Tolerance In Percent:						
-5.000 to 5.000						
Heat Sink Material:						
Steel						
Heat Sink Length:						
10.000 inches						
Heat Sink Width:						
10.000 inches						
Heat Sink Height:						
10.000 inches						
Heat Sink Thickness:						
0.040 inches						
Ambient Tempurature In Deg Celsius At Full Rated Power:						
40.0						
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:						
300.0						
Inclosure Method:						
Encapsulated						
Terminal Type:						
Terminal Type: Tab, solder lug						
Tab, solder lug						
Tab, solder lug Terminal Length:						
Tab, solder lug Terminal Length: 0.656 inches						
Tab, solder lug Terminal Length: 0.656 inches Body Length:						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width:						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches Power Dissipation Rating In Watts:						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches Power Dissipation Rating In Watts: 20.000 heat sink						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches Power Dissipation Rating In Watts: 20.000 heat sink Terminal Width:						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches Power Dissipation Rating In Watts: 20.000 heat sink Terminal Width: 0.250 inches						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches Power Dissipation Rating In Watts: 20.000 heat sink Terminal Width: 0.250 inches Mounting Hole Size:						
Tab, solder lug Terminal Length: 0.656 inches Body Length: 2.000 inches Body Width: 0.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.312 inches Power Dissipation Rating In Watts: 20.000 heat sink Terminal Width: 0.250 inches Mounting Hole Size: 0.260 inches						

N/a

NSN 5905-00-080-3892

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A001a0